



Model Number	Frequency (GHz)	Bandwidth (MHz)	Ins Loss (dB,Max)	Isolation (dB,Min)	VSWR (Max)	Operating Temp(°C)	Reverse Power(W)	Size L*W*H(mm)	Connector Type
CC-201J	1-2	Full	0.7	15	1.40	-15--+60	30	70*80*21	SMA/N
CC-301A	2-4	Full	0.6	16	1.40	-30--+70	20	32*34*18	SMA/N
CC-501H	3-6	Full	0.6	16	1.40	-30--+70	20	25.4*27.5*13	SMA
CC-601K	4-8	Full	0.6	18	1.30	-30--+70	20	20*26*14	SMA
CC-901K	6-12	Full	0.6	16	1.40	-40--+75	20	16*21*13	SMA
CC-701A	8-12	Full	0.5	20	1.25	-40--+75	10	15*19*13	SMA
	12-18	Full	0.6	18	1.35				
CC-1201A	8-18	Full	0.8	16	1.50	-40--+75	10	15*21*13	SMA

Note:All the above data are obtained at room temperature.

ELEADING TECHNOLOGIES LTD

F5102, Yunshenchu, Yuanlin Rd., Shatoujiao, Shenzhen, China. Zip: 518081

Phn.86-755-2528 5648 Fax.2528 5629. sales@eleadingchina.com

www.eleadingchina.com