



| Model Number | Frequency (GHz) | Bandwidth (MHz) | Ins Loss (dB,Max) | Isolation (dB,Min) | VSWR (Max) | Operating Temp(°C) | Reverse Power(W) | Size L*W*H(mm) | Connector Type |
|--------------|-----------------|-----------------|-------------------|--------------------|--------------|--------------------|------------------|----------------|----------------|
| CC-201F | 2-3.5 | 200 400 | 0.3 0.4 | 23 20 | 1.20 1.20 | -30-+70 | 20 | 25*25*15 | SMA |
| CC-401A | 3.5-6.5 | 300 600 | 0.3 0.4 | 23 20 | 1.20 1.20 | -40-+75 | 20 | 16*21*14 | SMA |
| CC-401A S | 3.5-6.5 | 300 | 0.6 | 50 | 1.20 | -40-+75 | 20 | 32*21*14 | SMA |
| CC-401D | 3.5-6.5 | 300 600 | 0.3 0.4 | 23 20 | 1.20 1.20 | -40-+75 | 20 | 20*24*18 | SMA/N |
| CC-701A | 6.5-18 | 300 1000 | 0.3 0.4 | 23 20 | 1.20 1.20 | -40-+75 | 10 | 15*19*13 | SMA |

Note: All the above data are obtained at room temperature.

ELEADING TECHNOLOGIES LTD

F5102, Yunshenchu, Yuanlin Rd., Shatoujiao, Shenzhen, China. Zip: 518081

Phn. 86-755-2528 5648 Fax. 2528 5629. sales@eleadingchina.com

www.eleadingchina.com