



Model Number	Frequency (GHz)	Bandwidth (MHz)	Ins Loss (dB,Max)	Isolation (dB,Min)	VSWR (Max)	Operating Temp(°C)	Reverse Power(W)	Size L*W*H(mm)	Connector Type
CD-0302A	0.3-0.4	30	0.3	23	1.20	-15-+60	150	52*57.5*16	TAB
CD-0402A	0.4-0.5	30	0.3	23	1.20	-15-+60	150	44*45.5*15.6	TAB
CD-0702	0.4-0.6	10	0.3	23	1.20	-15-+60	150	35*38*14.7	TAB
	0.6-0.8	30				-30-+70			
CD-0702D	0.4-0.6	30	0.4	23	1.20	-15-+60	150	35*38*13	TAB
CD-102C1-100	0.75-1.0	25	0.3	23	1.20	-30-+70	100	31.7*31.7*6.8	TAB
CD-0902B	0.8-1.2	25	0.35	23	1.20	-30-+70	30	20*20*8.6	TAB
CD-0902C	0.902-0.928	Full	0.3	23	1.20	-30-+70	30	φ 23.1*6.8	TAB
CD-102	0.8-1.2	70	0.3	23	1.20	-30-+70	100	30*33*11.5	TAB
	0.8-1.0	25							
CD-102C-60	1.7-2.2	70	0.3	23	1.20	-30-+70	100	25.4*25.4*6.8	TAB
	0.8-1.4	25							
CD-102J	1.0-1.4	200	0.4	20	1.20	-30-+70	100	25.4*25.4*12	TAB
	0.8-1.4	25							
CD-102J1	1.4-2.4	70	0.3	23	1.20	-30-+70	100	25.4*25.4*12	TAB
		200							
CD-102A	0.95-2.5	70	0.3	23	1.20	-30-+70	100	25.4*28.5*12	TAB
		200							
CD-202B	1.4-2.4	70	0.3	23	1.20	-30-+70	60	20*25.4*12	TAB
CD-202G1	1.7-2.5	70	0.3	23	1.20	-30-+70	60	19*19*8.2	TAB
CD-202H	1.7-2.5	70	0.3	22	1.20	-30-+70	60	19*19*5.6	TAB
CD-202C2	2.01-2.025	Full	0.25	20	1.20	-30-+70	60	12.7*12.7*6.4	TAB

Note: All the above data are obtained at room temperature.

ELEADING TECHNOLOGIES LTD

F5102, Yunshenchu, Yuanlin Rd., Shatoujiao, Shenzhen, China. Zip: 518081

Phn. 86-755-2528 5648 Fax. 2528 5629. sales@eleadingchina.com

www.eleadingchina.com