



Model Number	Frequency (GHz)	Bandwidth (MHz)	Ins Loss (dB,Max)	Isolation (dB,Min)	VSWR (Max)	Operating Temp(°C)	Reverse Power(W)	Size L*W*H(mm)	Connector Type
CD-202K	2-3.5	200	0.3	23	1.20	-30+70	20	25*26*11.5	TAB
		400	0.4	20	1.25				
CD-302	2-3.5	200	0.3	23	1.20	-30+70	20	20*25*11.5	TAB
CD-302C	3-6	300	0.3	23	1.20	-30+70	20	19*19*7.7	TAB
CD-302C2	3.1-3.5	Full	0.4	18	1.30	-30+70	20	12.7*12.7*6.4	TAB
	3.5-5	200	0.4	20	1.25				
CD-402A	3.5-6.5	300	0.3	23	1.20	-40+75	20	16*22*10.5	TAB
		600	0.4	20	1.20				
CD-502C	4.4-8	600	0.5	20	1.25	-40+75	10	12.7*12.7*6	TAB
CD-702-C1	4.4-8	300	0.4	23	1.20	-40+75	10	12.7*17*8	TAB
		600	0.5	20	1.25				
CD-802	7-18	300	0.3	23	1.20	-40+75	10	12.7*17*8	TAB
		1000	0.4	20	1.20				
CD-1002A	8-18	300	0.3	23	1.20	-40+75	10	8.9*12.5*7.8	TAB
		1000	0.4	20	1.25				

Note: All the above data are obtained at room temperature.

ELEADING TECHNOLOGIES LTD

F5102, Yunshenchu, Yuanlin Rd., Shatoujiao, Shenzhen, China. Zip: 518081

Phn. 86-755-2528 5648 Fax. 2528 5629. sales@eleadingchina.com

www.eleadingchina.com