



Model Number	Frequency (GHz)	Bandwidth (MHz)	Ins Loss (dB,Max)	Isolation (dB,Min)	VSWR (Max)	Operating Temp(°C)	Size L*W*H(mm)	Waveguide Type
CWG-320-8B	26.5-40	1000	0.3	20	1.25	-40+80	8*16*23	WR28
CWG-320-10	26.5-40	500	0.3	25	1.15	-40+80	10*24.5*19.1	WR28
		1000	0.3	20	1.25			
CWG-320-10D	26.5-40	500	0.3	25	1.15	-40+80	10*24.5*32	WR28
		1000	0.3	20	1.25			
CWG-320-15	26.5-40	1000	0.3	23	1.20	-40+80	15*25.4*19.1	WR28
CWG-320-20	26.5-40	3000	0.5	18	1.30	-40+80	20*26*19.1	WR28
CWG-400-19	32.9-50.1	1000	0.6	23	1.20	-40+80	19*20*19.1	WR22
		2000	0.6	20	1.25			
CWG-500-10	39.2-59.6	1000	0.6	23	1.20	-40+80	10*24.5*19.1	WR18
		2000	0.6	20	1.25			
CWG-500-19	39.6-59.6	1000	0.6	23	1.20	-40+80	19*19*19.1	WR18
		2000	0.6	20	1.25			
CWG-900-10A	84-100	1000	0.8	23	1.20	-40+80	10*25*19.1	WR10
		2000	1.0	18	1.30			

Note: All the above data are obtained at room temperature.

ELEADING TECHNOLOGIES LTD

F5102, Yunshenchu, Yuanlin Rd., Shatoujiao, Shenzhen, China. Zip: 518081

Phn. 86-755-2528 5648 Fax. 2528 5629. sales@eleadingchina.com

www.eleadingchina.com