



Model Number	Frequency (GHz)	Bandwidth (MHz)	Ins Loss (dB,Max)	Isolation (dB,Min)	VSWR (Max)	Operating Temp(°C)	Reverse Power(W)	Size L*W*H(mm)	Connector Type
IC-101A	0.95-2.5	70	0.3	25	1.20	-30+70	10	25.4*28.5*20	SMA/N
	1.0-2.5	200	0.4	20	1.25				
IC-101A-B	0.95-2.5	70	0.3	25	1.20	-30+70	100	25.4*38.5*20	SMA/N
	1.0-2.5	200	0.4	20	1.25				
IC-101A-S1	0.95-2.5	70	0.3	25	1.20	-30+70	10	25.4*28.5*15	SMA
	1.0-2.5	200	0.4	20	1.25				
IC-101AS	0.95-2.5	70	0.6	50	1.20	-30+70	10	50.8*28.5*20	SMA/N
	1.0-2.5	200	0.8	40	1.25				
IC-101ES-XA	0.92-0.965	full	0.5	45	1.15	-10+85	125	62*33*9	QMAK
IC-101ES-XB	1.8-1.885	full	0.5	45	1.15	-10+85	125	62*33*9	QMAK
IC-101ES-XC	0.864-0.899	full	0.5	45	1.15	-10+85	125	62*33*9	QMAK
IC-101ES-XD	1.925-1.995	full	0.5	45	1.15	-10+85	125	62*33*9	QMAK
IC-101F	0.8-2.0	25	0.3	25	1.20	-30+70	10	25*25*15	SMA
	1.0-2.0	200	0.4	20	1.25				
IC-201B1	1.4-2.4	70	0.3	25	1.20	-30+70	10	20*25.4*15	SMA
IC-201BS	1.6-2.2	70	0.5	45	1.20	-30+70	10	46*32*20	SMA/N
IC-201BS1	1.6-2.2	70	0.5	45	1.20	-30+70	10	40*27*18	SMA
IC-201	1.8-3.0	200	0.3	25	1.20	-30+70	10	28*30*19	SMA/N
		400	0.4	23	1.20				
IC-201F	1.8-3.5	200	0.3	25	1.20	-30+70	10	25*25*15	SMA
		400	0.4	20	1.20				

Note: All the above data are obtained at room temperature.

ELEADING TECHNOLOGIES LTD

F5102, Yunshenchu, Yuanlin Rd., Shatoujiao, Shenzhen, China. Zip: 518081

Phn. 86-755-2528 5648 Fax. 2528 5629. sales@eleadingchina.com

www.eleadingchina.com