



Model Number	Frequency (GHz)	Bandwidth (MHz)	Ins Loss (dB,Max)	Isolation (dB,Min)	VSWR (Max)	Operating Temp(°C)	Reverse Power(W)	Size L*W*H(mm)	Connector Type
IC-201D	2-3.5	200	0.3	23	1.20	-30+70	10	20*25*14	SMA
IC-401	3.5-6.5	300	0.3	25	1.20	-40+75	10	16*26*15	SMA
		600	0.4	23	1.20				
IC-401D	3.5-6.5	300	0.3	25	1.20	-40+75	10	16*26*19	N
		600	0.4	23	1.20				
IC-501S1	5-7	300	0.6	50	1.20	-40+75	10	30*21*14	SMA
IC-601A	3.5-6.5	300	0.3	25	1.20	-40+75	10	16*26*13	SMA
		600	0.4	23	1.20				
IC-501F	5-8	300	0.3	25	1.20	-40+75	10	16*24*14	SMA
		600	0.4	23	1.20				
IC-801	7-18	500	0.3	25	1.20	-40+75	10	12*20*13	SMA
		1000	0.4	23	1.20				
IC-801F	7-18	500	0.3	25	1.20	-40+75	10	12*20*13	SMA
		1000	0.4	23	1.20				
IC-801F2	7-18	500	0.3	25	1.20	-40+75	10	12*23*19	N
		1000	0.4	23	1.20				
IC-1201S	7-18	500	0.5	50	1.20	-40+75	10	24*20*13	SMA

Note: All the above data are obtained at room temperature.

ELEADING TECHNOLOGIES LTD

F5102, Yunshenchu, Yuanlin Rd., Shatoujiao, Shenzhen, China. Zip: 518081

Phn. 86-755-2528 5648 Fax. 2528 5629. sales@eleadingchina.com

www.eleadingchina.com