



Model Number	Frequency (GHz)	Bandwidth (MHz)	Ins Loss (dB,Max)	Isolation (dB,Min)	VSWR (Max)	Operating Temp(°C)	Reverse Power(W)	Size L*W*H(mm)	Connector Type
ID-0102	0.2-0.25	8	0.6	16	1.40	+20-+60	100	50.5*64.5*15	TAB
ID-0102A	0.15-0.25	8	0.6	16	1.40	+20-+60	100	70*84*15	TAB
ID-0402A	0.4-0.5	30	0.3	25	1.20	-15-+60	10	44*45.5*15.6	TAB
ID-0402-100	0.4-0.5	30	0.3	25	1.20	-15-+60	100	44*54*15.6	TAB
ID-0402-150	0.4-0.5	30	0.4	23	1.20	-15-+60	150	44*57.5*15.6	TAB
ID-0402H-100	0.375-0.5	Full	0.8	16	1.40	-10-+60	100	42*52*9	TAB
ID-0702	0.4-0.6	10	0.3	25	1.20	-15-+60	10	35*38*14.7	TAB
	0.6-0.8	30	0.3	25	1.20	-30-+70			
ID-0702-100	0.4-0.6	10	0.3	25	1.20	-15-+60	100	35*46*12.5	TAB
	0.6-0.8	30	0.3	25	1.20	-30-+70			
ID-0702-150	0.4-0.6	10	0.3	25	1.20	-15-+60	150	35*50*12.5	TAB
	0.6-0.8	30	0.3	25	1.20	-30-+70			
ID-0702D	0.4-0.6	30	0.4	23	1.20	-15-+60	10	35*38*13	TAB
ID-0702D-100	0.4-0.6	30	0.4	23	1.20	-15-+60	100	35*46*13	TAB
ID-0902B	0.8-1.2	25	0.35	23	1.20	-30-+70	10	20*20*8.6	TAB
ID-0902BS	0.8-1.0	25	0.65	50	1.20	-30-+70	10	41*21*8.6	TAB
ID-0902S	0.8-1.2	70	0.5	50	1.20	-30-+70	10	60*46*13.6	TAB

Note: All the above data are obtained at room temperature.

ELEADING TECHNOLOGIES LTD

F5102, Yunshenchu, Yuanlin Rd., Shatoujiao, Shenzhen, China. Zip: 518081

Phn. 86-755-2528 5648 Fax. 2528 5629. sales@eleadingchina.com

www.eleadingchina.com