



Model Number	Frequency (GHz)	Bandwidth (MHz)	Ins Loss (dB,Max)	Isolation (dB,Min)	VSWR (Max)	Operating Temp(°C)	Reverse Power(W)	Size L*W*H(mm)	Connector Type
IDJ-102-E	0.8-1.2	70	0.3	25	1.20	-30+70	10	30*33*12	TAB
IDJ-102C-100	0.8-1.0	25	0.3	23	1.20	-30+70	100	25.4*31.7*6.8	TAB
		100	0.5	20	1.25				
IDJ-102CS-100	0.8-1.0	70	0.3	23	1.20	-30+70	100	55.1*31.8*6.8	TAB
		100	0.5	50	1.20				
IDJ-102M3-100	0.824-1.0	25	0.3	23	1.20	-30+70	100	19*25.4*7.5	TAB
IDJ-102A	0.95-2.5	70	0.3	25	1.20	-30+70	10	25.4*28.5*12	TAB
		200	0.4	20	1.25				
IDJ-102J	0.8-1.4	25	0.3	25	1.20	-30+70	10	25.4*25.4*12	TAB
		200	0.4	20	1.20				
IDJ-102J1	1.4-2.4	70	0.3	25	1.20	-30+70	10	25.4*25.4*12	TAB
		200	0.4	20	1.20				
IDJ-102JS-E	0.8-1.8	25	0.5	50	1.20	-30+70	10	50*25.4*12	TAB
IDJ-102JS-100	0.8-1.8	25	0.5	50	1.20	-30+70	100	50*33.4*12	TAB

Note: All the above data are obtained at room temperature.

### ELEADING TECHNOLOGIES LTD

F5102, Yunshenchu, Yuanlin Rd., Shatoujiao, Shenzhen, China. Zip: 518081

Phn. 86-755-2528 5648 Fax. 2528 5629. [sales@eleadingchina.com](mailto:sales@eleadingchina.com)

[www.eleadingchina.com](http://www.eleadingchina.com)