



| Model Number | Frequency (GHz) | Bandwidth (MHz) | Ins Loss (dB,Max) | Isolation (dB,Min) | VSWR (Max) | Operating Temp(°C) | Reverse Power(W) | Size L*W*H(mm) | Connector Type |
|--------------|-----------------|-----------------|-------------------|--------------------|--------------|--------------------|------------------|----------------|----------------|
| ID-102K | 1.805-1.625 | full | 0.4 | 20 | 1.20 | -30+70 | 10 | 15*16.5*6.6 | TAB |
| ID-0902B1 | 1.5-2.0 | 70 | 0.3 | 23 | 1.20 | -30+70 | 10 | 20*20*9 | TAB |
| ID-0902B3 | 0.99-1.13 | full | 0.5 | 20 | 1.25 | -30+70 | 10 | 20*20*9.1 | TAB |
| ID-202D-E | 1.4-2.4 | 70 200 | 0.3 0.4 | 25 20 | 1.20 1.25 | -30+70 | 10 | 20*24.4*12 | TAB |
| ID-202DS-E | 1.7-1.9 | 70 | 0.6 | 45 | 1.20 | -30+70 | 10 | 35*23.5*12 | TAB |
| ID-202G-C1 | 1.7-2.5 | 30 100 | 0.3 0.3 | 25 23 | 1.20 1.20 | -30+70 | 10 | 19*19*8.2 | TAB |
| ID-202G-100 | 1.7-2.5 | 30 100 | 0.3 0.3 | 25 23 | 1.20 1.20 | -30+70 | 100 | 19*27*8.2 | TAB |
| ID-202H-5 | 1.7-2.8 | 70 | 0.3 | 22 | 1.20 | -30+70 | 5 | 19*19*5.6 | TAB |
| ID-202F-100 | 1.7-2.8 | 70 | 0.3 | 23 | 1.20 | -30+70 | 100 | 19*25.4*5.6 | TAB |
| ID-202FS-100 | 1.7-2.8 | 70 | 0.6 | 45 | 1.20 | -30+70 | 100 | 38.1*25.4*5.6 | TAB |
| ID-202H | 1.7-2.3 | 100 | 0.3 | 23 | 1.20 | -40+80 | 100 | 20*30*11.5 | TAB |
| ID-202H2 | 2.2-2.3 | full | 0.5 | 20 | 1.25 | -40+80 | 5 | 10*22.5*9.8 | TAB |
| ID-202T1 | 2.2-2.8 | 100 | 0.4 | 20 | 1.20 | -40+80 | 10 | 15*16.5*9.1 | TAB |

Note: All the above data are obtained at room temperature.

ELEADING TECHNOLOGIES LTD

F5102, Yunshenchu, Yuanlin Rd., Shatoujiao, Shenzhen, China. Zip: 518081

Phn. 86-755-2528 5648 Fax. 2528 5629. sales@eleadingchina.com

www.eleadingchina.com