



Model Number	Frequency (GHz)	Bandwidth (MHz)	Ins Loss (dB,Max)	Isolation (dB,Min)	VSWR (Max)	Operating Temp(°C)	Reverse Power(W)	Size L*W*H(mm)	Connector Type
ID-202	2-3	200	0.3	25	1.20	-30+70	10	20*30*11	TAB
		400	0.4	20	1.20				
ID-202K	2-3.5	200	0.3	25	1.20	-30+70	10	25*30*11.5	TAB
		400	0.4	23	1.20				
ID-302	2-3.5	200	0.3	23	1.20	-30+70	10	18*25*10	TAB
ID-302C	3-6	300	0.3	23	1.20	-30+70	10	19*19*7.7	TAB
		500	0.5	20	1.25				
ID-302C-100	3-6	300	0.3	23	1.20	-30+70	100	19*27*7.7	TAB
		500	0.5	20	1.25				
ID-302C2	3.1-3.5	Full	0.4	18	1.30	-20+90	5	12.7*12.7*6.4	TAB
ID-402	3.5-6.5	300	0.3	25	1.20	-40+75	10	16*26*10.5	TAB
		600	0.4	23	1.20				
ID-402S	3.5-6.5	300	0.5	50	1.20	-40+75	10	32*26*10.5	TAB
ID-402-C	4-7	300	0.3	25	1.20	-40+75	10	15*25*6	TAB
		600	0.4	23	1.20				
ID-402H	4-7	300	0.3	25	1.20	-40+75	10	14*22*9.5	TAB
		600	0.4	23	1.20				
ID-502A	5-7	200	0.3	25	1.20	-40+75	10	10*18*8	TAB
ID-502AS	5-7	100	0.5	50	1.20	-40+75	10	22*18*8	TAB

Note:All the above data are obtained at room temperature.

### ELEADING TECHNOLOGIES LTD

F5102,Yunshenchu,Yuanlin Rd.,Shatoujiao,Shenzhen,China.Zip:518081

Phn.86-755-2528 5648 Fax.2528 5629. [sales@eleadingchina.com](mailto:sales@eleadingchina.com)

[www.eleadingchina.com](http://www.eleadingchina.com)