



Model Number	Frequency (GHz)	Bandwidth (MHz)	Ins Loss (dB,Max)	Isolation (dB,Min)	VSWR (Max)	Operating Temp(°C)	Reverse Power(W)	Size L*W*H(mm)	Connector Type
ID-502B	5-7	300	0.3	25	1.20	-40+75	10	12*20*9.5	TAB
		600	0.4	23	1.20				
ID-502E	5-8	300	0.3	25	1.20	-40+75	10	12*20*6	TAB
		600	0.4	23	1.20				
ID-702-C1	4.4-8	300	0.3	25	1.20	-40+75	10	12.7*19*6	TAB
		600	0.4	20	1.20				
ID-802D	7-18	300	0.3	25	1.20	-40+75	10	12*20*9.5	TAB
		1000	0.4	23	1.20				
ID-1002E	7-18	300	0.3	25	1.20	-40+75	5	8.9*15*7.8	TAB
		1000	0.4	23	1.20				
ID-1002ES	7-18	500	0.5	50	1.20	-40+75	5	17.8*15*7.8	TAB
ID-1002G	7-18	300	0.3	25	1.20	-40+75	5	9*16*8	TAB
		1000	0.4	23	1.20				
ID-1002B	8-18	300	0.3	23	1.20	-40+75	5	8.9*13.5*7.8	TAB
		1000	0.4	20	1.20				
ID-1302-C1	10-13.3	Full	0.5	20	1.25	-40+75	5	7*19*5.7	TAB
ID-1302	9-18	100	0.4	23	1.20	-40+75	5	6.5*12.7*6.8	TAB
ID-1302S	9-18	100	0.6	50	1.20	-40+75	5	13*12.7*6.8	TAB

Note: All the above data are obtained at room temperature.

ELEADING TECHNOLOGIES LTD

F5102, Yunshenchu, Yuanlin Rd., Shatoujiao, Shenzhen, China. Zip: 518081

Phn. 86-755-2528 5648 Fax. 2528 5629. sales@eleadingchina.com

www.eleadingchina.com