



Model Number	Frequency (GHz)	Bandwidth (MHz)	Ins Loss (dB,Max)	Isolation (dB,Min)	VSWR (Max)	Operating Temp(°C)	Size L*W*H(mm)	Waveguide Type
IWG-320-5	26.5-40	1000	0.5	20	1.20	-40~+80	5*25.4*19.1	WR28
IWG-320-9.5A	37-40	Full	0.4	17	1.40	-40~+80	9.525*31.75*22.35	WR28
IWG-320-10	26.5-40	1000	0.3	25	1.20	-40~+80	10*28*19.1	WR28
		2000	0.35	22	1.22			
IWG-320-10B	26.5-40	1000	0.3	25	1.20	-40~+80	10*28*19.1	WR28
		2000	0.35	22	1.22			
IWG-320-12.7L	26.5-40	3000	0.4	20	1.25	-40~+80	12.7*31.75*19.1	WR28
IWG-320-12.7L1	26.5-40	3000	0.4	20	1.25	-40~+80	12.7*32*19.56	WR28
IWG-320-15	26.5-40	1000	0.3	25	1.20	-40~+80	15*28*19.1	WR28
IWG-320-20	33.4-36.6	Full	1.0	40	1.25	-40~+80	20*28*19.1	WR28
IWG-320-30	33.4-36.6	Full	1.5	60	1.25	-40~+80	30*28*19.1	WR28
IWG-400-10	32.9-50.1	1000	0.6	25	1.20	-40~+80	10*26*19.1	WR22
		2000	0.6	23	1.25			
IWG-500-10	39.2-59.6	1000	0.6	25	1.20	-40~+80	10*25.5*19.1	WR18
		2000	0.6	23	1.25			
IWG-900-10A	84-100	1000	0.8	23	1.25	-40~+80	10*22*19.1	WR10
		2000	1.0	20	1.30			

Note: All the above data are obtained at room temperature.

### ELEADING TECHNOLOGIES LTD

F5102, Yunshenchu, Yuanlin Rd., Shatoujiao, Shenzhen, China. Zip: 518081

Phn. 86-755-2528 5648 Fax. 2528 5629. [sales@eleadingchina.com](mailto:sales@eleadingchina.com)

[www.eleadingchina.com](http://www.eleadingchina.com)