



Model Number	Frequency (GHz)	Bandwidth (MHz)	Ins Loss (dB,Max)	Isolation (dB,Min)	VSWR (Max)	Operating Temp(°C)	Size L*W*H(mm)	Waveguide Type
IWG-84-36	7.7-8.4	Full	0.3	23	1.20	-40+80	36*75.5*48	WR112
IWG-84-69.2	7.25-8.4	Full	0.4	20	1.25	-40+80	69.2*83.3*44.5	WR112
IWG-100-70	10-11	Full	0.4	20	1.15	0+70	70*42*42	WR90
IWG-100-28	8-12.4	300	0.2	30	1.15	-40+80	28*56*42	WR90
		1000	0.3	23	1.20			
IWG-120-25	10-15	500	0.25	25	1.15	-40+80	25*52*38	WR75
		1000	0.3	23	1.20			
IWG-120-28M	10-15	500	0.25	25	1.15	-40+80	28*52*38	WR75
		1000	0.3	23	1.20			With sealing groove
IWG-140-21	12-18	500	0.3	25	1.15	-40+80	21*52*33.3	WR62
		1000	0.3	23	1.20			

Note: All the above data are obtained at room temperature.

ELEADING TECHNOLOGIES LTD

F5102, Yunshenchu, Yuanlin Rd., Shatoujiao, Shenzhen, China. Zip: 518081

Phn. 86-755-2528 5648 Fax. 2528 5629. sales@eleadingchina.com

www.eleadingchina.com